

Fundamental Study on Density-Based Topology Optimization Methods in Electromagnetic Fields

Taiki Kuze
Hideaki Nagamine
Tadashi Yamaguchi

(Gifu University)

2026/05/14 JUSW2026

Yamaguchi-Nagamine Laboratory, Gifu University, Japan


Outline

- Density-Based Topology Optimization Methods
- Background
- Purpose
- Propose Methods
- Analysis Model
- Consideration
- Conclusion

Yamaguchi-Nagamine Laboratory, Gifu University, Japan

Density-Based Topology Optimization Methods

Topology optimization methods is widely used in the field of design on electromagnetic devices.



Yamaguchi·Nagamine Laboratory, Gifu University, Japan

Background

Density-based topology optimization has the following issues:

- Inactive sensitivities at density bounds ($\rho = 0$ or 1)
- Vanishing sensitivity in low-density regions


These problems degrade convergence and solution quality

Yamaguchi·Nagamine Laboratory, Gifu University, Japan

① *Inactive sensitivities at density bounds*

Sensitivity may suggest decreasing density at $\rho = 0$ or increasing density at $\rho = 1$

- Inactive sensitivity updates
- Causes slow convergence



Yamaguchi·Nagamine Laboratory, Gifu University, Japan

② *Vanishing sensitivity in low-density regions*

Permeability interpolation:

$$\mu = \mu_0 \{1 + (\mu_r - 1) \rho^n\}$$

$$\frac{\partial \mu}{\partial \rho} \propto n \rho^{n-1}$$

- Gradient vanishes as $\rho \rightarrow 0$
- Design variables fail to update
- Optimization stagnates

Yamaguchi·Nagamine Laboratory, Gifu University, Japan

Purpose

To improve both:

- Update quality (Eliminating unnecessary updates)
- Update quantity (Ensuring gradient availability)

→ Achieve effective design variable updates

Yamaguchi·Nagamine Laboratory, Gifu University, Japan

Propose Methods

For Problem 1

Sensitivity Enhancement : Method(a)

For Problem 2

**Avoidance of zero sensitivity (Introduction of ρ_{\min})
: Method(b)**

→ Simultaneous control of update quality and quantity

Yamaguchi·Nagamine Laboratory, Gifu University, Japan

The Method (a) : Sensitivity Enhancement

Conditional sensitivity:


$\rho = 0$ and $\partial W / \partial \rho > 0 \rightarrow$ set to 0

$\rho = 1$ and $\partial W / \partial \rho < 0 \rightarrow$ set to 0

\rightarrow Removes unphysical updates

Effects:

- Improving convergence stability
- Eliminating unnecessary updates



Yamaguchi·Nagamine Laboratory, Gifu University, Japan

The Method (b) : Avoidance of Zero Sensitivity

Introduce minimum density ρ_{\min}

$$\mu(\rho) = \frac{(1 - \rho^n)\mu_{\text{air}} + (\rho^n - \rho_{\min}^n)\rho_{\text{iron}}}{1 - \rho_{\min}^n}$$


$$\mu(\rho_{\min}) = \mu_{\text{air}}$$

$$\mu(1.0) = \mu_{\text{iron}}$$

\rightarrow Restrict: $\rho \geq \rho_{\min}$

Effects:

- Preventing zero gradient
- Ensuring updates of design variables



Search domain
for the solution

Yamaguchi·Nagamine Laboratory, Gifu University, Japan


Integration of Methods

method(a): eliminates unnecessary updates
 method(b): ensures necessary updates

(a) only:
 → update becomes insufficient

(b) only:
 → noisy updates remain

(a) + (b):
 → stable and continuous update





Yamaguchi·Nagamine Laboratory, Gifu University, Japan

Analysis Model (1)

To verify the effectiveness of the proposed methods, we apply them to the following model:

2D C-core model : Objective : Minimize electromagnetic force



Yamaguchi·Nagamine Laboratory, Gifu University, Japan

Analysis specifications


Analysis specifications

Number of elements	13,650
Number of nodes	13,926
Number of elements in design domain	2,400
Current density	2.0e6
Relative permeability of armature	1,000

- Bilinear quadrilateral elements
 - Fortran implementation
 - ICCG Method
- Convergence criterion : 10^{-12}


Yamaguchi · Nagamine Laboratory, Gifu University, Japan

Result : Objective value



Yamaguchi · Nagamine Laboratory, Gifu University, Japan

Result : *Number of Iterations*



Yamaguchi-Nagamine Laboratory, Gifu University, Japan

Result : *Optimized Shape*



Conventional



(a)



(b)



(a+b)

Yamaguchi-Nagamine Laboratory, Gifu University, Japan

Conclusion

- Two issues in density-based update are identified
 - Corresponding methods are proposed
- Both update quality and quantity are improved
- Optimization performance is enhanced

Yamaguchi·Nagamine Laboratory, Gifu University, Japan

Thank you for listening.

Yamaguchi·Nagamine Laboratory, Gifu University, Japan